

# Autosense & Autosense Voice Blood Glucose Monitoring Systems



Dcont *diabetes control*

77 Elektronika

1116 Budapest,  
Fehérvári út 98.  
HUNGARY

Sales Hotline: +36 1 481-0139

Tel.: +36 1 206-1480

Fax: +36 1 206-1481

Email: sales@e77.hu

www.e77.hu



For self-testing

IVD



No manual coding  
required to make  
testing easier,  
faster and safer



Small sample  
volume, virtually  
pain-free



Rapid test results  
displayed on easy  
to read large LCD,  
excellent accuracy



Two measurement  
units, optional whole  
blood or plasma  
equivalent calibration



Large memory  
capacity with  
averaging function



Easy and hygienic  
strip ejection to avoid  
blood contact



Special flags: pre-meal,  
post-meal, sport etc.



Data downloading  
capability to PC



Alternate Site Testing  
(blood collection from  
fingertips, palms,  
forearms)



Alarm function  
to suggest testing



Optional talking  
function\*  
(AutoSense Voice)

## AutoSense easy-to-use kit:

1. AutoSense Blood Glucose Meter with battery
2. Adjustable lancing device with disposable lancets
3. Instructions for Use
4. Quick Reference Guide
5. Check-strip
6. Carrying Case



## AutoSense Test Strips:

- Capillary blood sample absorption
- Viewing window
- Shelf life: 24 month
- 10, 25 or 50 strips in a vial



## Wireless Data Download Device

Optical interface for downloading your glucose profile to a local PC simply and quickly



## Diatransfer 2

- diabetes data management software
- blood glucose profile display
- multi-patient mode for professionals

TECHNICAL SPECIFICATIONS Autosense / (AutoSense Voice)	
Type:	advanced auto-coding biosensor technology
Sample:	min. 0.5 µl capillary whole blood
Operating range:	temperature: 10-40 °C relative humidity: < 90% altitude: below 3000 m hematocrit: 30-55%
Measuring range:	1.1 - 33.3 mmol/l (20-600 mg/dl)
Average test time:	5 seconds
Memory capacity:	last 500 test data with date and time
Talking function:	in AutoSense Voice
Automatic switch on:	upon insertion of test strip
Automatic power off:	in 2 minutes after the last button activation
Warning and error signals:	out of measuring range (Low / High); hypoglycemia; insufficient sample detection; low / high temperature; low battery
Alarm function:	daily 3 alarms
Batteries:	1 pc. 3V, type: CR2032 / (2 pcs. 3V, type: CR2032)
Battery life:	1 year or 1500 measurements / (1 year or 1000 measurements)
Display:	LCD
Interfaces:	Infrared port to LiteLink Data Download Device
Dimensions:	55x100x21 mm
Weight:	60 g / (90 g) with batterie(s)

**77 Elektronika Kft.**

77 Elektronika Kft. is a major global developer, manufacturer, and supplier of in vitro diagnostic medical devices, mainly urine analyzers, blood glucose meters, and their consumables. The products are supplied throughout the world under the 77 Elektronika brand and as OEM products for market-leading multinational companies. 77 Elektronika was established in 1986 and is headquartered in Hungary (EU). The company is committed to providing superior products and services to the complete satisfaction of its customers.

## Easy, accurate and quick testing of blood glucose level:

